

General Sterling Questions

- All cylinders and Barrels are shipped with 2 stainless steel, plastisol coated clamps, except model 66 that is supplied with 1 clamp.
- Complete motor cartridge includes poly pro motor gear and male twistlock connector.
- Model 44, 46 and 56 have cylinder mesh ends. Model 66 and 612 have a solid dimpled pattern on inside of cylinder gear.
- Model 60 oblique baskets have basket handles that attach on the outside, all other 6" baskets handles attach from the inside.
- Barrel prices include a cylinder, choice of standard motor speed (30 or 60 rpm), choice of standard rod or ball danglers, choice of mesh or square hole panels. Square hole panels not available on model 24,44,46,56 barrels.
- 12" baskets standard for Nobles dryer. Specify NH if basket will be used to dry in New holland dryers.
- Model 44, 46 and 56 cylinders require 1/2" screws. Model 66 thru 1224 require 7/8" long screws. Titanium screws are dull and have a cross slot head, stainless screws are shiny and have a phillips type head.
- To determine what barrel you have - measure inside dimensions of cylinder i.e. model 46 is 4" diameter x 6" long. – see Chart Below:

Model 44	non removable red motor cartridge	2 curved panels, 1 door
Model 46		2 curved panels, 1 door
Model 56	"	3 curved panels, 1 door
Model 66	removable red motor cartridge	2 curve panels, 1 door
Model 612	"	2 curved panels, 1 door
Model 8512	"	8 flat panels, 1-(2 flat panel) door
Model 8512 Delta	"	3 flat panels, 2 curve panels, 1 curved door
Model 918	"	8 flat panels, 1-(2 flat panel) door
Model 918 Delta	"	3 flat panels, 2 curve panels, 1 curved door
Model 1018	"	10 flat panels, 1-(2 flat panel) door
Model 1024	"	10 flat panels, 1-(2 flat panel) door
Model 1224	"	13 flat panels, 1-(2 flat panel) door